



**Verified Carbon
Standard**

ADJUSTED WATER MANAGEMENT IN RICE CULTIVATION IN TONGCHENG CITY



Document Prepared by Shanghai Libra Investment & Management Co., Ltd

Project Title	Adjusted Water Management in Rice Cultivation in Tongcheng City
Version	01
Date of Issue	09-October-2020
Prepared By	Shanghai Libra Investment & Management Co., Ltd
Contact	Physical address: Room H, Floor 20, Aibang Mansion, No.585 Lingling Road, Xuhui District, Shanghai, China Telephone: +86-21-64693022 Email: kvz@libracarbon.com Website: www.libracarbon.com

CONTENTS

1	PROJECT DETAILS	4
1.1	Summary Description of the Project	5
1.2	Sectoral Scope and Project Type	5
1.3	Project Eligibility	5
1.4	Project Design	5
1.5	Project Proponent	6
1.6	Other Entities Involved in the Project	5
1.7	Ownership	6
1.8	Project Start Date	7
1.9	Project Crediting Period	7
1.10	Project Scale and Estimated GHG Emission Reductions or Removals	8
1.11	Description of the Project Activity	8
1.12	Project Location	11
1.13	Conditions Prior to Project Initiation	11
1.14	Compliance with Laws, Statutes and Other Regulatory Frameworks	12
1.15	Participation under Other GHG Programs	11
1.16	Other Forms of Credit	11
1.17	Additional Information Relevant to the Project	12
2	SAFEGUARDS	15
2.1	No Net Harm	16
2.2	Local Stakeholder Consultation	16
2.3	Environmental Impact	18
2.4	Public Comments	18
2.5	AFOLU-Specific Safeguards	18
3	APPLICATION OF METHODOLOGY	20
3.1	Title and Reference of Methodology	20
3.2	Applicability of Methodology	20
3.3	Project Boundary	22
3.4	Baseline Scenario	22
3.5	Additionality	23
3.6	Methodology Deviations	23
4	QUANTIFICATION OF GHG EMISSION REDUCTIONS AND REMOVALS	24

4.1	Baseline Emissions.....	23
4.2	Project Emissions	24
4.3	Leakage	25
4.4	Net GHG Emission Reductions and Removals.....	25
5	MONITORING	32
5.1	Data and Parameters Available at Validation	31
5.2	Data and Parameters Monitored	32
5.3	Monitoring Plan	36

1 PROJECT DETAILS

1.1 Summary Description of the Project

The project changing from continuously flooded to intermittent flooded condition during rice cultivation is conducted in Tongcheng City, Anhui Province of China. Anhui Province, located in eastern China with a total acreage of 13,228ha for double-cropping rice. Without the implementation of this project, which provides ditches to conduct intermittently flooded method, the backward continuously flooded method would be continued, so the scenario that rice was cultivated by continuously flooded method is the baseline scenario. Since the organic matter in rice soil under flooded condition can emit a large amount of methane (CH₄) because of anaerobic decomposition, the intermittent flooded method is more beneficial to water conservation, production increase and methane emission removal than the continuously flooded.

This project solved the problems of excessive water used during rice cultivation which results in not only large amount of methane (CH₄) emissions but also low rice productivity by replacing the continuously flooded method with intermittent flooded method, which shortens the period of anaerobic decomposition of soil organic matter. In this case, the CH₄ emission can be declined by an average of 48%.¹ Hence, with the proposed project activity, an estimated amount of GHG emission reduction 4.54 tCO₂e/ha for double-cropping rice is expected.

The implementation of the project is expected to reduce the GHG emissions amounting to 1,258,341 tCO₂e in 21 years, with an average annual GHG emission removal of 59,921 tCO₂e.

This project aims to:

- Sequester greenhouse gas and mitigate climate changes;
- Increase the rice productivity resulting in higher living standard of local farmers;
- Provide more job opportunities, especially women workers;
- Invest a part of profit to improve the local medical care;
- Use a proportion of benefits to improve the local children's education.

1.2 Sectoral Scope and Project Type

¹ Dr. Reiner Wassmann (2016). Coordinator, Climate Change Research. International Rice Research Institute. Available from: r.wassmann@irri.org

The project is developed under VCS scope 14 “Agriculture, Forestry and Other Land Use (AFOLU)” with an activity category of Improved Cropland Management (ICM) under Agricultural Land Management (ALM). The project is not a grouped project.

1.3 Project Eligibility

This project produces methane (CH₄) emission reductions, which is eligible under the scope of VCS program. Besides, this project activity is supported by the CDM small-scale methodology: *Methane emission reduction by adjusted water management practice in rice cultivation* which is approved under a VCS approved GHG program – United Nations Clean Development Mechanism.

1.4 Project Design

This project is a single project activity instance.

Eligibility Criteria

The project is not a grouped project.

1.5 Project Proponent

Organization name	Hefei Luyu Agricultural Technology Co., Ltd
Contact person	Yiliang Chen
Title	Manager
Address	Room 2212, Building C, Xinhua International Square, No.320 Qianshan Road, Hefei City, Anhui Province, China
Telephone	+86-1331686686
Email	mail@luyunongye.com

1.6 Other Entities Involved in the Project

Organization name	Shanghai Libra Investment & Management Co., Ltd
Role in the project	Consultant
Contact person	Shaohui Zhong
Title	Manager

Address	Room H, Floor 20, Aibang Mansion, No.585 Lingling Road, Xuhui District, Shanghai, China
Telephone	+86-21-64693022
Email	kvz@libracarbon.com

1.7 Ownership

The ownership of the rice paddies of the agricultural land management project belongs to the farmers, which has been confirmed by the local government and agricultural bureau. Since these rice paddies are all legal agricultural fields, and the ownership is clear, there is no dispute over land ownership in the project site.

Furthermore, they also have right to authorize Hefei Luyu as a representative of the project owner and Hefei Luyu only has the right to make decisions about the carbon reduction project including the type of the carbon credit project to be developed, the sales target, the sales price, etc.²

1.8 Project Start Date

According to VCS standard, the project start date is the date on which activities that lead to the generation of GHG emission reductions or removals are implemented, for this project, the project start date is 10-February-2018 when the land preparation was started.

1.9 Project Crediting Period

The crediting period of this project will be using a 7-year, twice renewable crediting period, for a combined total project crediting period of 21 years from 10-February -2018 to 09-February-2039, and the project lifetime³ is 30 years from 29-January-2018 to 28-January-2048.

1.10 Project Scale and Estimated GHG Emission Reductions or Removals

Project Scale	
Project	√

² Source: carbon reduction project cooperation agreement signed between the farmers and Hefei Luyu.

³ Which is indicated in the file named 'Implementation Plan of Tongcheng National Agricultural Comprehensive Development High Standard Farmland Construction Project in 2017' from Tongcheng Agricultural Bureau

Large project

Year	Estimated GHG emission reductions or removals (tCO ₂ e)
10-February -2018 to 09-February-2019	59,921
10-February -2019 to 09-February-2020	59,921
10-February -2020 to 09-February-2021	59,921
10-February -2021 to 09-February-2022	59,921
10-February -2022 to 09-February-2023	59,921
10-February -2023 to 09-February-2024	59,921
10-February -2024 to 09-February-2025	59,921
10-February -2025 to 09-February-2026	59,921
10-February -2026 to 09-February-2027	59,921
10-February -2027 to 09-February-2028	59,921
10-February -2028 to 09-February-2029	59,921
10-February -2029 to 09-February-2030	59,921
10-February -2030 to 09-February-2031	59,921
10-February -2031 to 09-February-2032	59,921
10-February -2032 to 09-February-2033	59,921
10-February -2033 to 09-February-2034	59,921
10-February -2034 to 09-February-2035	59,921
10-February -2035 to 09-February-2036	59,921
10-February -2036 to 09-February-2037	59,921
10-February -2037 to 09-February-2038	59,921
10-February -2038 to 09-February-2039	59,921
Total estimated ERs	1,258,341 tCO₂e
Total number of crediting years	21 years
Average annual ERs	59,921 tCO₂e

1.11 Description of the Project Activity

The project changing from continuously flooded to intermittent flooded condition during rice cultivation is conducted in Tongcheng City, Anhui Province of China. Anhui Province, located in eastern China, is one of the major rice-producing provinces in China. At the same time, Tongcheng City is an impoverished city where the annual household income of farmers is only 11803.3⁴ CNY and most of it is used to maintain the survival. In this case, they lacked funds to build ditches for applying intermittently flooded method. So, continuously flooded method was used in rice paddies, which means fields have standing water throughout the rice growing season and may only dry out for harvest. However, the organic matter in rice soil under flooded condition can emit a large amount of methane (CH₄) because of anaerobic decomposition. In contrast, there are at least once aeration period of more than three days, except for end-season drainage, during the cropping season by conducting intermittently flooded method after the cement ditches is built in this project activity. Since the CH₄ in rice paddies is produced by the anaerobic decomposition of organic matter after the flooding, allowing the field to drain halts CH₄ production, which happens in anaerobic condition, reducing the total quantity of CH₄ released during the cropping season. Moreover, the intermittently flooded method is more beneficial to water conservation, production increase and methane emission removal than the continuously flooded. The project aims to replace the traditional cultivation method by intermittent flooded method for GHG removal whilst contributing to Sustainable Development Goals (SDGs) in the project zone. 13,228 ha (198,420 Mu⁵) of rice paddies are changed to apply intermittently flooded method in Tongcheng City, where the rice used to be cultivated under continuously flooded condition.

The project is located in Tongcheng City, with a total population of nearly 760,000. All the rice paddies belong to the farmers and the village committees manage the paddies on behalf of farmers. Hefei Luyu Agricultural Technology Co., Ltd. (hereafter referred to as Hefei Luyu) has been fully authorized by all the village committees to act as the project proponent to implement project management and monitoring, and to sell VCUs generated from the project so that Hefei Luyu consolidates the offset resources into sizeable forestry offset projects. Hefei Luyu shall profit-share with the farmers from selling VCUs. The implementation of the project activity generates 59,921 tCO₂e/year and contributes to 7 SDGs.

The main objectives of the project are to improve the productivity of rice and contribute to the sustainable development and SDGs, including:

1. Goal 1-No Poverty

⁴ Source: The ex ante survey report in Tongcheng City

⁵ A Chinese metric unit of area, 1ha = 15 Mu.

The project increases yield by applying intermittently flooded method during cultivation in rice paddies, so the farmers in impoverished counties can see a higher net return and get out of poverty.

2. Goal 2-Zero Hungry

The project provides canals, reservoirs and pumps for practicing intermittently flooded method, which helps in increase the rice production.

3. Goal 4-Quality Education

A part of the profit of this project would be used to buy more books for the local children, which provides them with quality education.

4. Goal 5-Gender Equality

The project provides training to women who wish to participate in and facilitate more ownership of resources and access to economic opportunities.

5. Goal 8-Decent Work and Economic Growth

Field staff personnel would be hired from the local villages to conduct intermittently flooded water regime in the project area.

6. Goal 13-Climate Action

The project generates 59,921 tCO₂e of emission reductions in rice paddies by practicing intermittently flooded water regime, which makes contribution to the climate problems.

The implementation schedule of this project is listed as follows:

Date	Milestone (s) in the project's development and implementation
29-May-2017	Hefei Luyu Agricultural Technology Co., Ltd held a general meeting of their stockholders and they decided to develop this project as a carbon trading project.
18-November-2017	Construction of high standard rice fields was started
10-February-2018	The project activity was started, which means the planting was started
09-October-2020	The draft PD was completed

1.12 Project Location

The project is located in Tongcheng City, which is a prefecture-level city within Anqing City of Anhui Province, China. Now, it has jurisdiction over 1 state-level development zone, 12 towns and 3 streets, which are Xindu Town, Shuanggang Town, Qingcao Town, Fangang Town, Jinshen Town, Xizi Hu Town, Kongcheng Town, Lvting Town, Daguan Town, Tangwan Town, Xunyu Town, Huangjia Town, Longmian Street, Wenchang Street and Longteng Street. The geographical coordinates of the project are between 116°40' and 117°09' east longitude and between 30°40' and 31°16' north latitude.

The location of the project activity in Tongcheng City of Anqing City which is illustrated in Figure 1-2. According to VCS standard, Tongcheng City is defined as the project zone, and the rice paddies applied intermittent flooded water regime in Tongcheng City is defined as the project area. The boundaries of the project area and project zone are shown in Figure 1-3, and the KML file has also been submitted.



Figure 1-1 The map of China



Figure 1-2 The map of Anhui Province



Figure 1-3 The map of project zone – Tongcheng City

1.13 Conditions Prior to Project Initiation

The project zone, Tongcheng City, is located in the southwest of Central Anhui Province, with Dabie Mountains to the west and the Yangtze River to the south. It is adjacent to Lujiang County and Zongyang County in the east, Shucheng County in the north, Qianshan County in the west, Huaining County and Yixiu District in the south. It has a total area of 1,472 square kilometers.

Prior to the project initiation, the basic conditions of the project zone are summarized as follows:

Before the implementation of this project, the irrigation and drainage ditch of rice paddies in Tongcheng City was made up of soil, which is not enough to make the irrigation and drainage controllable. Furthermore, the topography of the rice paddies was uneven, making it difficult to maintain uniform irrigation depth during cultivation period. In this case, the rice was planted under continuously flooded condition, which gained relatively lower productivity, because rice has different water requirement at each growing stage.

1.14 Compliance with Laws, Statutes and Other Regulatory Frameworks

The project conforms to all kinds of regulations in the agricultural field, which are listed as below:

PRC Constitution, PRC Agricultural Law, Law of the PRC on Land Administration, Implementing Regulations of the Law of the PRC on Land Administration, Law of the PRC on Rural Land Contracting, PRC Production Safety Law, and PRC Labour Law.

According to the Inspection and Acceptance Report of the project, the project has complied with the above regulations and laws during the construction period and will be subject to regular inspection by local government during the implementation period to ensure continuous compliance.

1.15 Participation under Other GHG Programs

1.15.1 Projects Registered (or seeking registration) under Other GHG Program(s)

The project has not been registered or is seeking registration under any other GHG programs.

1.15.2 Projects Rejected by Other GHG Programs

The project has not been rejected by any other GHG programs.

1.16 Other Forms of Credit

1.16.1 Emissions Trading Programs and Other Binding Limits

The project is not involved in an emission trading program or any other mechanism that includes GHG allowance trading.

1.16.2 Other Forms of Environmental Credit

The project has not sought or received another form of GHG-related environmental credit.

1.17 Additional Information Relevant to the Project

Leakage Management

According to the applied methodology: *Methane Emission Reduction by Adjusted Water Management Practice in Rice Cultivation*, any effects of the project activity on GHG emissions outside the project boundary are deemed to be negligible and do not have to be considered under this methodology. So, leakage does not need to be considered.

Commercially Sensitive Information

None of the project documents will be considered commercially sensitive information, and all the documentation is available to any stakeholders.

Sustainable Development

The Project provides many benefits that will help achieve China's Sustainable Development Goals, a set of 17 universal goals covering the thematic areas of environmental, economic and social development.



The project contributes to achieving sustainable development as following:

- High yield brings extra income and improves the living standard of local farmers (Goal 1 mentioned as Section 1.11);

- Increase the rice productivity alleviates hunger problem (Goal 2 mentioned as Section 1.11);
- Use a proportion of benefits to improve the local children's education (Goal 4 mentioned as Section 1.11);
- Women are given priority for employment and their social status is raised (Goal 5 mentioned as Section 1.11);
- Provide more job opportunities for local farmers (Goal 8 mentioned as Section 1.11);
- Sequester greenhouse gas and mitigate climate changes (Goal 13 mentioned as Section 1.11).

Goal 1	Higher income
Type of Impact	The impact is a positive impact as increasing yield and new job opportunities created by the change of rice cultivation method.
Affected Stakeholder Group(s)	Farmers participated in the project
Expected achievement	Agricultural farming is a major source of income for the farmers in the project zone. Therefore, the increase of yield is of great importance for them. In addition, farmers could get extra pay because of more job opportunities, which could help them get out of poverty.

Goal 2	Increase in rice yield
Type of Impact	The impact is a positive impact as the rice grown using the intermittently flooded method can increase its production.
Affected Stakeholder Group(s)	Farmers participated in the project
Expected achievement	Rice is an important staple for local farmers and even the whole country, so higher yields could solve the hunger problem to some extent.

Goal 4	Help in quality education
Type of Impact	The impact is a positive impact as the project will help to improve the local education.
Affected Stakeholder Group(s)	Farmers participated in the project
Expected achievement	A part of the profit of this project shall be used to buy some books for the local children, which provides them with quality education.

Goal 5	Help in gender equality
Type of Impact	The impact is a positive impact as the project provides training to women who wish to participate in and facilitates more ownership of resources and access to economic opportunities.
Affected Stakeholder Group(s)	Women workers within the project area
Expected achievement	Some new job occupations would be created by this project, and the women shall be given priority for employment which improves their social status.

Goal 8	More job opportunities and growth of local economy
Type of Impact	The impact is a positive impact as the project provides more job opportunities for practicing the intermittently flooded method. At the same time, higher rice production could bring growth in local economy.
Affected Stakeholder Group(s)	Farmers within the project area

Expected achievement	In order to practice the intermittently flooded method, some better irrigation and drainage facilities should be provided, such as the canals, reservoirs and pumps. In this case, a large number of job occupations could be created. Therefore, the male adults working outside the county would come back to make contribution to their hometown.
Goal 13	CH ₄ emission reduction
Type of Impact	The impact is a positive impact as CH ₄ emissions generated by soil organic matter under anaerobic conditions is reduced. The impact is an actual impact which is a direct consequence of the project activity.
Affected Stakeholder Group(s)	Farmers within the project area
Expected achievement	It is expected to reduce 59,921 tCO ₂ e every year by conducting this project, because the duration of anaerobic decomposition of soil organic matters in rice paddies is shorten by replacing continuously flooded with intermittently flooded.

Further Information

There is no any further information that may have a bearing on the eligibility of the project, the net GHG emission reductions or removals, or the quantification of the project's net GHG emission reductions or removals.

2 SAFEGUARDS

2.1 No Net Harm

The potential negative environmental and socio-economic impacts and steps to mitigate them have been summarized in the following table:

Environmental		Socio-Economic	
Potential Negative Impacts	Actions	Potential Negative Impacts	Actions

Improper pesticide application would be harmful to natural environment, including polluting soil, water and air conditions, as well as the habitat of the wildlife.	In this project activity, adhere to the principle of "prevention first", and give priority to the use of biological and mineral pesticides in the selection of pesticides, thus reducing the harm	Before the project, the income from rice cultivation was not high, so the local labor force was lost.	After the project activity was implemented, the productivity of rice was improved and more job opportunities were created, which means higher income, thus, many migrant workers are more likely to return home.
Excessive application of nitrogen fertilizer can also pollute the soil and even the air.	With this project implementation, the amount of nitrogen fertilizer used in rice paddies cannot exceed the optimal amount recommended.	If the intermittently flooded method cannot be conducted strictly during rice cultivation within the project area, then the yield would not be great and the income will not be increased.	The relevant training should be conducted every year and the technician should also give timely guidance during every monthly inspection.

2.2 Local Stakeholder Consultation

Stakeholder consultations include an ex ante surveys and stakeholder meetings, requiring stakeholders to present their opinions on project design and their willingness to participate.

Before the project started, Anhui Academy of Social Sciences conducted stakeholder meetings to ask their willingness of participation. Anhui Academy of Social Sciences organized a team of people to interview the village representatives, relevant governmental officials and distribute the questionnaires to gather local farmers' opinions. A total of 100 questionnaires were distributed, and 100 were collected. The surveys took 1 week and completed on 17 June 2017. The feedback collected is summarized below:

- Most farmers are well aware of the benefits of adjusted water management during rice cultivation. They understand that the intermittently flooded method can reduce methane emissions, save water resource and increase the rice productivity.

- Prior to the meeting, most local farmers had never heard of carbon trading, VCS or carbon credits. After the introduction, they strongly agreed that the project should be registered as a carbon reduction project and participate in the carbon trading market.
- Local farmers believe that the project can 1) create jobs; 2) get more benefits from selling carbon credits; 3) reduce methane emissions, save water resource and increase the rice productivity; and 4) improve the social status of women by hiring them to be technicians. Therefore, the stakeholders have no opinions on the project implementation, and there is no need to change the project design.
- The local agricultural bureau is very clear about the benefits of the intermittently flooded cultivation method and understands that carbon trading can make projects more sustainable.

Table 2-1 Survey Results Summary Sheet

Question	Survey Result
How many people in your family? How much is the annual income? What are the main economic sources?	The average number of people is 3.65 in one family and the average annual income is 11803 CNY. The main economic source is planting rice.
Do you think the intermittently flooded water regime is good for rice cultivation?	It is favourable.
What do you know about the benefits of the intermittently flooded water regime?	Reduce methane emissions, save water resource and increase the rice productivity
What industries does your family member work in?	Labor and farming
What kind of production activities does your family do?	Crop farming
What is your educational level?	70% are middle school level, 20% are high school level and the rest are primary school level.
Is the land ownership involved in the project clear?	Yes.
Did you know carbon trading before?	Most people had never known.
Through the staff's introduction to carbon trading, do you support this project's	Definitely support.

application for development as a carbon reduction project?	
If this project is successfully applied for development as a carbon reduction project, what benefits do you think can be brought?	Create more job opportunities for economic benefits, improve the local environment, reduce methane emissions, save water resource, and increase the rice productivity.
Do you support hiring women to participate in rice cultivation and management in this project?	Yes.
Do you think there is anything that needs to be improved in the design or implementation of this project? Please provide your valuable comments.	No comments.

2.3 Environmental Impact

According to the Environmental Impact Assessment Law of the People's Republic of China, this project does not require any environmental impact assessments.

2.4 Public Comments

It will be supplemented after the project is publicized.

2.5 AFOLU-Specific Safeguards

1. Stakeholder Identification

This stakeholder's identification starts by listing all the people or groups who might have an influence over or be impacted by a project. The local village committees and village officials were considered as the key informants and focus groups who know best about the local farmers. In June 2017, the project proponent and Anhui Academy of Social Sciences held a consultant meeting with local village committees before the project start, and the main purpose of the meeting was to identify the stakeholders in the project.

- 1) Village residents: (including 4,410 local farmers of which 2,866 are females, accounting for about 65 percent)

In Tongcheng City, a total of 4,410 farmers have been directly affected by the activities of the project. In addition, the rice paddies in the project area belong to these farmers. Hence, the village committees collected the opinions and consent of the farmers in respective villages through face-to-face meetings before deciding to apply to the local governments'

and agricultural bureaus for using intermittently flooded method through participation in the Plan of High Standard Farmland Construction⁶ (hereinafter referred to as HSFC). These farmers were also responsible for signing the cooperation agreements with the project proponents to ensure the proper development of the project.

Since June 2017, before the project started, the village committees conducted a survey of the local farmers' willingness to participating in the Plan of HSFC for applying the intermittently flooded method during rice cultivation. This was done through meetings and interviews with farmers. All the farmers agreed to use this advanced cultivation method in the end.

The meeting held on June 2017 was attended by the representatives of Tongcheng Agricultural Bureau, the representatives of Hefei Luyu the representatives of farmers, and the representatives of the village committee. The representatives of Tongcheng Agricultural Bureau also organized a meeting to solicit suggestions from farmers for the implementation of project activities and their willingness to participate in rice cultivation.

This project activity has greatly benefited the local farmers and could only carry out with the farmers' consent. Hence, all the farmers within the project zone are recognized to be stakeholders in the project.

2) Agricultural Bureau of Tongcheng City

The techniques of intermittently flooded method are provided by the local agricultural bureau, which inspects successful rice cultivation. In this respect, the farmers, the committees, the local governments granting permission and local agricultural bureau providing advice and inspections, are all identifies as relevant stakeholders in this project.

3) Local governments of Tongcheng City

The local administration is responsible for the local social and environmental management. They are responsible and accountable to all local farmers for any violation of their rights.

4) Village committees

They are responsible for collecting opinions from the respective locals and villages with the project proponent or agricultural bureaus.

The results of identified stakeholders will be publicly announced on VCS website as part of the draft PD which can be accessed by everyone, in case there is any other person who may consider themselves as one of the project's stakeholders, they can directly contact the project owner for consultation.

⁶ This Plan is government-led, involving the construction of ditches and the leveling of rice paddies, and voluntary participation is applied for by farmers

2. Potential Risks and Measures

Potential risks to stakeholders	● Sudden diseases occur during drainage and irrigation, including heart disease, etc. ● Natural disaster
Measures to mitigate it	All these potential risks should be told to the stakeholders in advance and some simple first aid measures also need to be communicated to farmers during training to reduce the injuries.

3 APPLICATION OF METHODOLOGY

3.1 Title and Reference of Methodology

The small-scale methodology AMS-III.AU: *Methane Emission Reduction by Adjusted Water Management Practice in Rice Cultivation/version 4.0* is used. Also, the project proponent shall apply the “General guidelines for SSC CDM methodologies/version 23.0”.

In addition, since the reporting and verification shall be done on the basis of samples of the log-books from the farmers, the *Standard for Sampling and Surveys for CDM Project Activities and Programme of Activities/version 8.0* and the *Guideline for Sampling and Surveys for CDM Project Activities and Programme of Activities/version 4.0* are used.

The TOOL 21 “Demonstration of Additionality of Small-scale Project Activities (version 13.1)” is used to demonstrate the additionality.

3.2 Applicability of Methodology

As mentioned in Section 3.1, the methodology applied in this project is AMS-III.AU (version 4.0) which is applicable under the following conditions:

Conditions required by methodology	Applicability of this project
a) Rice cultivation in the project area is predominantly characterized by irrigated, flooded fields for an extended	According to the result of baseline surveys ⁷ , rice cultivation in the project area is predominantly characterized by irrigated,

⁷ Source: The ex ante investigation report of Tongcheng City in 2017 from Anhui Academy of Social Sciences

period during the growing season, i.e. farms whose water regimes can be classified as upland or rainfed and deep water are not eligible to apply this methodology. This shall be shown from a representative survey conducted in the geographical region of the proposed project or by using national data.	flooded fields for an extended period during the growing season.
b) The project rice fields are equipped with controlled irrigation and drainage facilities such that both during dry and wet season, appropriate dry/flooded conditions can be established on the fields;	With the project, the rice fields are equipped with controlled irrigation and drainage facilities such that intermittently flooded method can be conducted.
c) The project activity does not lead to a decrease in rice yield. Likewise, it does not require the farm to switch to a cultivar that does not been grown before;	The type of rice planted in this project is very common and the project activity is not subject to any local regulatory restrictions, so it will not lead to a decrease in rice yield.
d) Training and technical support during the cropping season that delivers appropriate knowledge in field preparation, irrigation, drainage and use of fertilizer to the farmer is part of the project activity and is to be documented in a verifiable manner (e.g. protocol of trainings, documentation of on-site visits). In particular, the project proponent is able to ensure that the farmer by himself or through experienced assistance is able to determine the crop's supplemental N fertilization need. The applied method shall assess the fertilizer needs using for example a leaf colour chart or photo sensor or testing stripes. Alternatively, a procedure to ensure efficient fertilization considering the specific cultivation conditions in the project area	The regular training and technical support shall be held every February during the crediting period of this project.

	backed by scientific literature or official recommendations shall be used;	
e)	Project proponents shall assure that the introduced cultivation practice, including the specific cultivation elements, technologies and use of crop protection products, is not subject to any local regulatory restrictions;	Any activities involved in this project are legal.
f)	Except the case where the default value approach indicated as follows, “Emission reductions using IPCC tier 1 approach or default values” is chosen for emission reductions calculations, project proponents have access to infrastructure to measure CH ₄ emissions from reference fields using closed chamber method and laboratory analysis;	Since “Emission reductions using IPCC tier 1 approach or default values” is chosen for emission reductions calculations, project proponent has already set the closed chamber in the reference fields and made the plan of monitoring.
g)	Aggregated annual emission reductions of all fields included under one project activity shall be less than or equal to 60 kt CO ₂ equivalent.	Those rice paddies belong to the local farmers, covering a total of 13,228 hectares, and 59,921 tCO ₂ e is expected to be generated every year, which is below 60 kt CO ₂ e.

As described above, this small-scale methodology AMS-III.AU (version 4.0) is applicable to the proposed activity.

3.3 Project Boundary

Source	Gas	Included?	Justification/Explanation
Baseline	CO ₂	No	Not included in this project
	CH ₄	Yes	Baseline emissions consist of the CH ₄ emissions.
	N ₂ O	No	Due to the optimized N fertilization practice regulated by the methodology, N ₂ O emissions do not significantly deviate from the baseline emissions and hence are not considered.
	Other	No	Not included in this project

Source	Gas	Included?	Justification/Explanation
Project	CO ₂	No	Not included in this project
	CH ₄	Yes	Project emissions consist of the CH ₄ emissions, which will still be emitted under the changed water regime.
	N ₂ O	No	Due to the optimized N fertilization practice regulated by the methodology, N ₂ O emissions do not significantly deviate from the baseline emissions and hence are not considered.
	Other	No	Not included in this project

The rice paddies applied intermittently flooded water regime in Tongcheng City is defined as the project area, also the project boundary where the cultivation method and water regime are changed. The map of the project boundary is provided as the Figure 3-1, and the yellows sections show the specific project areas.




Figure 3-1 the map of the project boundary

3.4 Baseline Scenario

According to the small-scale methodology: *Methane Emission Reduction by Adjusted Water Management Practice in Rice Cultivation*, the baseline scenario is the continuation of the current practice which is continuously flooded water regime without any organic amendment during rice cultivation in the project fields in this project (see further details in Section 3.5).

3.5 Additionality

Investment barrier

In the absence of the project activity, the living standard of Tongcheng rural residents is poor and the economy is backward, so it is difficult for them to build the cement ditches for timely drainage and irrigation according to the growth need of rice.

Technological barrier

The original water regime used during rice cultivation, continuously flooded method, is more convenient for farmers to practice, because it only requires that the fields should be flooded throughout the whole season and there is no need to pay close attention to the growth status of rice for appropriate drainage and irrigation. Thus, without this project, farmers are more willing to growing rice by old method, although higher emissions would be resulted. Besides, the poor economy also limits their access to advanced technology about intermittently flooded water regime, which requires regularly drainage and irrigation. However, Tongcheng City is also a major rice planting county in Anhui, in the last few decades, they have used continuously flooding method to plant rice. In this case, the rice yield is not satisfied, resulting in lower income. In this cycle, the county could not be developed, and the labor force gradually surplus. As a result, a large proportion of the young workforce choose to leave the hometown for seeking job opportunities in the more developed counties. The lack of economic improvement leads to inadequate health care and inadequate education.

In general, this project has both investment and technological barriers.

3.6 Methodology Deviations

No deviations from the procedures indicated by the methodology have been made.

4 QUANTIFICATION OF GHG EMISSION REDUCTIONS AND REMOVALS

4.1 Baseline Emissions

As described in methodology AMS-III.AU (version 4.0) mentioned above, the baseline scenario is the continuation of the current practice, e.g. continuously flooded rice cultivation in the project fields, the baseline emissions are estimated as follows:

$$BE_y = \sum_s BE_s \quad (1)$$

$$BE_y = \sum_{g=1}^G EF_{BL,s,g} \times A_{s,g} \times 10^{-3} \times GWP_{CH_4} \quad (2)$$

Where:

Parameters	Description
BE_y	Baseline emissions in year y (tCO ₂ e)
BE_s	Baseline emissions from project fields in season s (tCO ₂ e)
$EF_{BL,s,g}$	Baseline emissions factor of group g in season s (kgCH ₄ /ha per season)
$A_{s,g}$	Area of project fields of group g in season s (ha)
GWP_{CH_4}	Global warming potential of CH ₄ (tCO ₂ e/tCH ₄)
g	Group g, covers all project fields with the same cultivation pattern (G = total number of groups)

4.2 Project Emissions

According to the applied methodology AMS-III.AU (version 4.0), the project emissions within the project boundary are calculated as follows:

$$PE_y = \sum_s PE_s \quad (3)$$

$$PE_s = \sum_{g=1}^G EF_{P,s,g} \times A_{s,g} \times 10^{-3} \times GWP_{CH_4} \quad (4)$$

Where:

Parameters	Description
PE_y	Project emissions in year y (tCO ₂ e)
PE_s	Project emissions from project fields in season s (tCO ₂ e)
PE_s	Project emission factor of group g in season s (kgCH ₄ /ha per season)

4.3 Leakage

According to the applied methodology AMS-III.AU (version 4.0), any effects of the project activity on GHG emissions outside the project boundary are deemed to be negligible and do not considered under this methodology. So, leakage does not need to be considered in this project.

4.4 Net GHG Emission Reductions and Removals

The emission reductions achieved by the project activity shall be calculated as the difference between the baseline and the project emissions, which is also used as post-emission reduction:

$$ER_s = BE_s - PE_s \quad (5)$$

Where:

Parameters	Description
ER_s	Emission reductions in season s (tCO ₂ e)

According to the applied methodology AMS-III.AU (version 4.0), for the ex ante estimation of emission reductions within the project design document prior to the project implementation, project proponent shall refer to own field experiments or estimate baseline and project emissions with the help of national data or IPCC tier 1 default values for emission and scaling factors.

In this project, using the IPCC tier 1 approach but undertaking measurements to determine baseline emission factors for continuously flooded fields, as per the following formula:

$$ER_y = EF_{ER} \times A_y \times L_y \times 10^{-3} \times GWP_{CH_4} \quad (6)$$

$$EF_{ER} = EF_{BL} - EF_P \quad (7)$$

$$EF_{BL} = EF_{BL,c} \times SF_{BL,w} \times SF_{BL,p} \times SF_{BL,o} \quad (8)$$

$$EF_P = EF_{BL,c} \times SF_{P,w} \times SF_{P,p} \times SF_{P,o} \quad (9)$$

Where:

Parameters	Description
ER_y	Emission reductions in year y (t CO ₂ e)

EF_{ER}	Adjusted daily emission factor (kgCH ₄ /ha/day). Alternatively, seasonal emission factor (kg CH ₄ /ha/season ⁸) may be determined
A_y	Area of project fields in year y (ha)
L_y	Cultivation period of rice in year y (days/year). This is not applicable when seasonal emission factor is determined.
GWP_{CH_4}	Global warming potential of CH ₄ (t CO ₂ e/t CH ₄)
EF_{BL}	Baseline emission factor (kg CH ₄ /ha/day) or (kg CH ₄ /ha/season)
EF_p	Project emission factor (kg CH ₄ /ha/day) or (kg CH ₄ /ha/season)
$EF_{BL,c}$	Baseline emission factor for continuously flooded fields without organic amendments (kg CH ₄ /ha/day) or (kg CH ₄ /ha/season)
$SF_{BL,w}$ or $SF_{p,w}$	Baseline or project scaling factors ⁹ to account for the differences in water regime during the cultivation period
$SF_{BL,p}$ or $SF_{p,p}$	Baseline or project scaling factors to account for the differences in water regime during the pre-season before the cultivation period
$SF_{BL,o}$ or $SF_{p,o}$	Baseline or project scaling factors should vary for both type and amount of organic amendment applied

However, the baseline emission factor for continuously flooded fields without organic amendments ($EF_{BL,c}$) can be determined ex ante prior to the start of the project activity, in this case, the ex ante value should be used to calculate emission reduction during the crediting period. It should be measured by using closed chamber in three reference fields which are chosen in the project area. The closed chamber measurement requires the involvement of technicians trained by experts from Anhui Agricultural Bureau. This chamber made of commercially available PVC material needs to be used in conjunction with a fixed base. The base made of non-corrosive material and it should have bores in the submerged section to allow water exchange between inside and outside. Besides, the base should be installed at least 24 hours before the first sampling and remains for the whole season. There are three auxiliaries within the chamber, which are thermometer for measuring the temperature inside the chamber, the fan (battery operated) inside the chamber for mix the inside air during sampling and the sampling port (the rubber stopper placed in a bore of the chamber). After

⁹ For all scaling factor used in this methodology, the average values in 2006 IPCC Guidelines for National Greenhouse Gas Inventories are chosen.

sampling the air inside the chamber, it should be stored in syringe (<24h) or evacuated vial (>24h) for laboratory analysis done by gas chromatograph with flame ionization detector (FID).

The details of the reference fields and the plan for the seasonal methane measurements before the start of the season is shown as following:

Table 4-1 The details of reference fields

Location	Kongcheng Town, Tongcheng City
Area	About 0.3ha of each
The type of rice	Hybrid rice
Climate	Subtropical humid monsoon climate
Soil	pH5.5-7.4 and the soil organic carbon is 2.53%
Water management	Continuously flooded ¹⁰
Fertilizer treatment	No any organic amendments

Table 4-2 The plan for the seasonal methane measurements

Field measurement	Laboratory analysis
The base should be buried before the transplanting	The samples should be analysed in laboratory every three times
First sampling should be taken after 24 hours from transplanting	
The measurement interval should be once per week	After final laboratory analysis is completed, the monitoring data of whole cropping season should be integrated and the emission factor should be calculated to complete the experimental report.
The last sampling should be taken 24 hours before harvest	

It is demonstrated by *The Report of Measuring Methane Emission Rate of Double-cropping Rice Paddies with Continuously Flooded Method by Closed Chamber in Tongcheng City in 2017* Anhui Agricultural Bureau (see further details in Section 5.1 below) that the baseline emission factor for continuously flooded fields without organic amendments ($EF_{BL,c}$) is 180 kg CH₄/ha/season for early season and 157.04 kg CH₄/ha/season for second season.

Besides, the IPCC default for $SF_{BL,w}$ or $SF_{P,w}$ is as follows:

Water regime during the cultivation period	$SF_{BL,w}$ or $SF_{P,w}$
--	---------------------------

¹⁰ Continuously flooded: fields have standing water throughout the rice growing season and may only dry out for harvest (end-season drainage)

Irrigated	Continuously flooded ¹¹	1
	Intermittently flooded-single aeration ¹²	0.60
	Intermittently flooded-multiple aeration ¹³	0.52

For the baseline scenario, the water regime is continuously flooded, so the $SF_{BL,w}$ is 1. As described in Section 1.11, the water regime of this project activity is intermittently flooded with multiple aeration, so the $SF_{P,w}$ is 0.52.

In addition, IPCC default for $SF_{BL,p}$ or $SF_{P,p}$ is provided in the following table.

Water regime prior to cultivation period	$SF_{BL,p}$ or $SF_{P,p}$
Non-flooded pre-season<180 days (indicating double cropping)	1
Non-flooded pre-season>180 days (indicating double cropping)	0.68

In the project area, all the rice cultivation is double cropping, so both $SF_{BL,p}$ and $SF_{P,p}$ are 1. Accordingly, since no amendments are applied under both baseline and project scenario, $SF_{BL,o}$ and $SF_{P,o}$ do not need to be considered.

Taking all the information above, the table below can be reached.

Parameters	Early Season	Second Season
$EF_{BL,c}$ (kg CH ₄ /ha/day)	1.5	1.51
$EF_{BL,c}$ (kg CH ₄ /ha/season)	180	157.04
$SF_{BL,w}$	1	
$SF_{P,w}$	0.52	

¹¹ Continuously flooded: fields have standing water throughout the rice growing season and may only dry out for harvest (end-season drainage)

¹² Single aeration: fields have a single aeration during the cropping season at any growth stage (except for end-season drainage)

¹³ Multiple aeration: fields have more than one aeration period during the cropping season (except for end-season drainage)

$SF_{BL,p} / SF_{P,p}$	1
GWP_{CH_4}	28
A_y (ha)	13,228
P.S. The GWP_{CH_4} is taken from the Fifth Assessment report, GHG Protocol	

Under this methodology, any effects of the project activity on GHG emissions outside the project boundary are deemed to be negligible and do not have to be considered, so the leakage of this project activity is zero.

Thus, for early season, the emission reduction should be calculated as follows:

$$EF_{BL} = EF_{BL,c} \times SF_{BL,w} \times SF_{BL,p} = 180 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1} \times 1 \times 1 = 180 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1}$$

$$EF_P = EF_{BL,c} \times SF_{P,w} \times SF_{P,p} = 180 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1} \times 0.52 \times 1 = 93.60 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1}$$

$$EF_{ER} = EF_{BL} - EF_P = 180 - 93.60 = 86.40 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1}$$

$$ER_y = EF_{ER} \times A_y \times 10^{-3} \times GWP_{CH_4} = 86.40 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1} \times 13,228 \text{ ha} \times 10^{-3} \times 28 = 32,001 \text{ tCO}_2e$$

Likely, for the later season, the emission reduction should be calculated as follows:

$$EF_{BL} = EF_{BL,c} \times SF_{BL,w} \times SF_{BL,p} = 157.04 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1} \times 1 \times 1 = 157.04 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1}$$

$$EF_P = EF_{BL,c} \times SF_{P,w} \times SF_{P,p} = 157.04 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1} \times 0.52 \times 1 = 81.66 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1}$$

$$EF_{ER} = EF_{BL} - EF_P = 157.04 - 81.66 = 75.38 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1}$$

$$ER_y = EF_{ER} \times A_y \times 10^{-3} \times GWP_{CH_4} = 75.38 \text{ kgCH}_4/\text{ha}^{-1} * \text{season}^{-1} \times 13,228 \text{ ha} \times 10^{-3} \times 28 = 27,919 \text{ tCO}_2e$$

Therefore, for a whole year, the emission reduction is $32,001 \text{ tCO}_2e + 27,919 \text{ tCO}_2e = 59,221 \text{ tCO}_2e$.

The ex ante calculations of baseline and project emissions are shown in excel and the results are summarized in the Table following.

Year	Estimated baseline emissions or removals (tCO ₂ e)	Estimated project emissions or removals (tCO ₂ e)	Estimated leakage emissions (tCO ₂ e)	Estimated net GHG emission reductions or removals (tCO ₂ e)

10-February -2018 to 09-February-2019	N/A ¹⁴	N/A	0	59,921
10-February -2019 to 09-February-2020	N/A	N/A	0	59,921
10-February -2020 to 09-February-2021	N/A	N/A	0	59,921
10-February -2021 to 09-February-2022	N/A	N/A	0	59,921
10-February -2022 to 09-February-2023	N/A	N/A	0	59,921
10-February -2023 to 09-February-2024	N/A	N/A	0	59,921
10-February -2024 to 09-February-2025	N/A	N/A	0	59,921
10-February -2025 to 09-February-2026	N/A	N/A	0	59,921
10-February -2026 to 09-February-2027	N/A	N/A	0	59,921
10-February -2027 to 09-February-2028	N/A	N/A	0	59,921
10-February -2028 to 09-February-2029	N/A	N/A	0	59,921
10-February -2029 to 09-February-2030	N/A	N/A	0	59,921
10-February -2030 to 09-February-2031	N/A	N/A	0	59,921
10-February -2031 to 09-February-2032	N/A	N/A	0	59,921
10-February -2032 to 09-February-2033	N/A	N/A	0	59,921

¹⁴ According to the CDM small-scale methodology: ***Methane emission reduction by adjusted water management practice in rice cultivation (v4.0)***, Para 5.8.1 Ex ante estimation of emission reductions, PP has chosen option 1 for the calculation of Ex ante ER, while the according to the Equation (6) $ER_y = EF_{ER} \times A_y \times L_y \times 10^{-3} \times GWP_{CH_4}$ in the methodology, the ex ante of ER value is calculated directly but not calculated by Baseline emissions minus project emissions. So PP provided N/A in the table in section 4.4.

10-February -2033 to 09-February-2034	N/A	N/A	0	59,921
10-February -2034 to 09-February-2035	N/A	N/A	0	59,921
10-February -2035 to 09-February-2036	N/A	N/A	0	59,921
10-February -2036 to 09-February-2037	N/A	N/A	0	59,921
10-February -2037 to 09-February-2038	N/A	N/A	0	59,921
10-February -2038 to 09-February-2039	N/A	N/A	0	59,921
Total	N/A	N/A	0	1,258,341

5 MONITORING

5.1 Data and Parameters Available at Validation

Data / Parameter	A_y
Data unit	ha
Description	Area of project fields in year y
Source of data	Field measurement
Value applied	The total area is 13,228ha
Justification of choice of data or description of measurement methods and procedures applied	N/A
Purpose of Data	The parameter is used to calculate the estimated net GHG removals.
Comments	N/A

Data / Parameter	GWP_{CH_4}
Data unit	t CO ₂ e/t CH ₄
Description	Global warming potential of CH ₄
Source of data	The number of GWP_{CH_4} is taken from the <i>Fifth Assessment report, GHG Protocol</i>
Value applied	28
Justification of choice of data or description of measurement methods and procedures applied	N/A
Purpose of Data	The parameter is used to calculate the estimated net GHG removals.
Comments	N/A

Data / Parameter	$EF_{BL,C}$
Data unit	kg CH ₄ /ha/day or kg CH ₄ /ha/season
Description	Seasonal baseline emission factor for continuously flooded fields without organic amendments
Source of data	The Report of Measuring Methane Emission Rate of Double-cropping Rice Paddies with Continuously Flooded Method by Closed Chamber in Tongcheng City in 2017.
Value applied	(1) 1.5 kg CH ₄ /ha/day or 180 kg CH ₄ /ha/season for early season rice; (2) 1.51 kg CH ₄ /ha/day or 157.04 kg CH ₄ /ha/season for later season rice;
Justification of choice of data or description of measurement methods and procedures applied	The report of Measuring Methane Emission Rate of Paddy Fields with Continuously Flooded Method by Closed Chamber in Tongcheng City for early season was completed in August 2017, while that for second season was completed in December 2017.
Purpose of Data	The parameter is used to calculate the baseline emission factor EF_{BL} .

Comments	N/A
-----------------	-----

Data / Parameter	$SF_{BL,w}$
Data unit	N/A
Description	Baseline scaling factors to account for the differences in water regime during the cultivation period
Source of data	It is chosen from 2006 IPCC Guidelines for National Greenhouse Gas Inventories.
Value applied	1
Justification of choice of data or description of measurement methods and procedures applied	Since the rice is cultivated under continuously flooded condition in baseline scenario, the 1 of value is used.
Purpose of Data	The parameter is used to calculate the baseline emission factor EF_{BL} .
Comments	N/A

Data / Parameter	$SF_{P,w}$
Data unit	N/A
Description	Project scaling factors to account for the differences in water regime during the cultivation period
Source of data	It is chosen from 2006 IPCC Guidelines for National Greenhouse Gas Inventories.
Value applied	0.52
Justification of choice of data or description of measurement methods and procedures applied	Since the rice is cultivated under intermittently flooded condition in project scenario, the 0.52 of value is used.
Purpose of Data	The parameter is used to calculate the project emission factor EF_P .

Comments	N/A
Data / Parameter	$SF_{BL,p}$
Data unit	N/A
Description	Baseline scaling factors to account for the differences in water regime in the pre-season before the cultivation period.
Source of data	It is chosen from 2006 IPCC Guidelines for National Greenhouse Gas Inventories.
Value applied	1
Justification of choice of data or description of measurement methods and procedures applied	Since the cultivation mechanism in rice field is double cropping in baseline scenario, the 1 of value is used.
Purpose of Data	The parameter is used to calculate the baseline emission factor EF_{BL} .
Comments	N/A

Data / Parameter	$SF_{P,p}$
Data unit	N/A
Description	Project scaling factors to account for the differences in water regime in the pre-season before the cultivation period.
Source of data	It is chosen from 2006 IPCC Guidelines for National Greenhouse Gas Inventories.
Value applied	1
Justification of choice of data or description of measurement methods and procedures applied	Since the cultivation mechanism in rice field is double cropping in project scenario, the 1 of value is used.

Purpose of Data	The parameter is used to calculate the baseline emission factor EF_p .
Comments	N/A

5.2 Data and Parameters Monitored

Data / Parameter	$A_{s,g}$
Data unit	ha
Description	Aggregated project area in a given season s
Source of data	To determine by collecting the project field sizes in a project database. Project proponent shall set up a database which holds data and information that allow an unambiguous identification of participating rice farms, including the size of field.
Description of measurement methods and procedures to be applied	Field measurement
Frequency of monitoring/recording	Every season
Value applied	N/A
Monitoring equipment	N/A
QA/QC procedures to be applied	General guidelines for SSC CDM methodologies
Purpose of data	The parameter is used to calculate the baseline emissions from project fields in season s (BE_s).
Calculation method	N/A
Comments	Only compliant farms are considered
Data / Parameter	$EF_{BL,s,g}$
Data unit	kg CH ₄ /ha per season
Description	Baseline emission factor of group g in a given season s

Source of data	Field measurements in baseline reference fields
Description of measurement methods and procedures to be applied	As per instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Frequency of monitoring/recording	Once a week. Regular measurements as per closed chamber method guidance, seasonally integrated
Value applied	N/A
Monitoring equipment	Closed chamber
QA/QC procedures to be applied	The implementation of methane measurement in rice fields shall be conducted by technicians trained by experts in this field. All the data should be cross-checked by technicians and experts.
Purpose of data	The parameter is used to calculate the baseline emissions from project fields in season s (BE_s).
Calculation method	N/A
Comments	N/A

Data / Parameter	$EF_{P,s,g}$
Data unit	kg CH ₄ /ha per season
Description	Project emission factor of group g in a given season s
Source of data	Field measurements in project reference fields
Description of measurement methods and procedures to be applied	As per instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Frequency of monitoring/recording	Once a week. Regular measurements as per closed chamber method guidance, seasonally integrated
Value applied	N/A
Monitoring equipment	Closed chamber

QA/QC procedures to be applied	The implementation of methane measurement in rice fields shall be conducted by technicians trained by experts in this field. All the data should be cross-checked by technicians and experts.
Purpose of data	The parameter is used to calculate the project emissions from project fields in season s (PE_s).
Calculation method	N/A
Comments	N/A

5.3 Monitoring Plan

Monitoring process

(1) Monitoring of farmers' compliance with project cultivation practice

In order to determine whether the project fields are cultivated according to intermittently flooded cultivation practice, and thus assure that measurements on the reference fields are representative for the emissions from the project fields, a cultivation logbook shall be maintained for all project fields. With the help of the logbook, all parameters, as following, that are part of the project cultivation practice shall be documented by the farmers:

- (a) Sowing date;
- (b) Fertilizer, organic amendments, and crop protection application (date and amount);
- (c) Water regime on the field (e.g. "dry/moist/flooded") and dates where the water regime is changed from one status to another;
- (d) Yield.

In addition, farmers shall state whether they have followed fertilization recommendations¹⁵ provided with the introduction of the adjusted water management practice.

Since the reporting and verification shall be done on the basis of samples of the logbooks from the farmers, according to the latest version of the "*Standard for sampling and surveys for CDM project activities and programme of activities (version 8.0)*", the process of sampling is shown as follows:

● Objectives and Reliability Requirements

This sampling plan is for 4,410 farmers involved in this project. The project had applied intermittently flooded water regime with the same type, same category and same technology.

¹⁵ The optimal amount of nitrogen fertilization is 9.5-10kg/mu recommended by Technical Guidelines for Intermittently Flooded Rice Cultivation Method in Anhui Province

After the implementation, this new water regime displaced the traditional continuously flooded method during rice cultivation in the project area. The farmers' logbooks should be sampled for assuring the project activity. In this case, the project proponent shall use 90/10 confidence/precision according to the sampling standard mentioned above.

● Target Population

From the description, the target population is the related 4,410 farmers planting the rice.

Table 5-1 the number of farmers in each town of Tongcheng City

Name of Town	The number of farmers
Shuanggang Town	152
Xindu Town	244
Jinshen Town	277
Xizi Hu Town	391
Fangang Town	474
Kongcheng Town	346
Lvting Town	611
Daguan Town	1,063
Qingcao Town	852
Total	4,410

● Sample Method

Since the farmers are numerous and scattered, the water regime used during rice cultivation is identical, stratified random sampling is adopted in order that each one can be selected with equal probability. The strata should be mutually exclusive: every element in the population must be assigned to only one stratum. The stratification requires that information on the stratification variable, e.g. survey sample farmer will be changed once per year. Simple random sampling method will be taken in each stratum by using Microsoft Excel.

● Sample Size

According to the “*Standard for sampling and surveys for CDM project activities and programme of activities (version 8.0)*”, the desired confidence level is 90% and the desired precision is 10%. Based on the statistical principles and sampling survey method, 314

samples should be sufficient to satisfy the desired confidence and precision. For mean value sampling, the required sampling quantity is calculated by the following steps:

$$n_1 = \frac{Z^2 \sigma^2}{d^2} \quad (10)$$

Step1:

Where:

Parameters	Description
Z	The symbol used in general formula for confidence intervals. The validation team confirms it is to be 1.645 when confidence interval is 90%
σ	The population standard deviation, which is not available to PP
d	The maximum error of estimate

Step 2: Deformation of basic formula

$$n_1 = \frac{Z^2 \sigma^2}{d^2} = \frac{Z^2 (\frac{\sigma^2}{X^2})}{d^2/X^2} = Z^2 V^2 / e^2 \quad (11)$$

Where:

Parameters	Description
V	the coefficient of variation, and $V = \sigma/X$. As population standard deviation σ shall be smaller than the sample mean value X , hence from conservative consideration point of view, making $V=1$ can get the biggest sample size. It is conservative
e	the relative sampling error, and $e = d/X$, which is the precision. In this case, $e=10\%$ as discussed above

Consequently, $n_1 = \frac{Z^2 V^2}{e^2} = \frac{1.645^2}{0.01} = 270.6$, and round up to 271.

Step 3: Correction based on population size

$$n_2 = \frac{n_1 N}{n_1 + N} \quad (12)$$

Where:

Parameters	Description
------------	-------------

N	The population size, it is 4,410 under project context
-----	--

Therefore,

$$n_2 = \frac{n_1 N}{n_1 + N} = \frac{271 \times 4410}{271 + 4410} = 255.31, \text{ and round up to be 256, it takes } n_2 = 256 \text{ is preferable.}$$

Step 4: Correction based on sampling approach

$$n_3 = B n_2 \quad (13)$$

Where:

Parameters	Description
B	The survey design effect

As discussed in *Procedures for Administering Data Collection and Minimizing Non-Sampling Errors*. The project adopts multi-stage sampling approach. In this case, $B \leq 1$ as per Sampling Design and Methodology. It's conservative consideration.

$$\text{Thus, } n_3 = B n_2 = 1 \times n_2 = 256$$

Step 5: Correction based on responding rate

$$n_4 = \frac{n_3}{r} \quad (14)$$

Where:

The responding rate is adopted to be less 90% according to investigation report.

$$\text{Thus, } n_4 = \frac{n_3}{r} = \frac{256}{90\%} = 284.44, \text{ round up to be 285.}$$

Step 6: Correction based on contingency consideration

$$n = 110\% \times n_4 \quad (15)$$

Where:

$$\text{Consequently, the sample size } n = 110\% \times n_4 = 110\% \times 285 = 313.5, \text{ round up to be 314.}$$

The calculation result for n is 314. Therefore, 314 sample logbooks from farmers will be selected from the sampling frame according to stratified sampling method at the beginning of each year during the crediting period. An inclusion of 314 samples in total, the sample size of each township was decided on the method of proportional distribution.

- Sampling Frame

In the investigation, sampling frame is worked out independently by taking town as sampling unit. Sampled group will be changed in each monitoring period. Firstly, calculate the ratio of farmers in every administrative town to the total population of Tongcheng City. According to the ratio of every town, calculate the sampling size of every town, and then set the amount of sampling 314 farmers, the actual sampling size is the ratio of every town multiply by 314.

Table 5-2. The sampling size of logbooks from farmers in each town of Tongcheng City

Name of Town	The number of farmers
Shuanggang Town	11
Xindu Town	18
Jinshen Town	20
Xizi Hu Town	28
Fangang Town	33
Kongcheng Town	25
Lvting Town	44
Daguan Town	75
Qingcao Town	60
Total	314

(2) Monitoring of baseline and project emissions

According to the applied methodology AMS-III.AU (version 4.0), post-emission reduction shall be calculated by the formulas (1) – (5) shown in Section 5.1 and Section 5.2 above. So, $EF_{BL,s,g}$ and $EF_{P,s,g}$ shall be measured by technicians based on the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5. In this project, there is only one field group, thus, three baseline reference fields and project reference fields should be selected respectively for methane emission measurement. Besides, project reference fields shall be established close to the baseline reference fields and begin with the growing season at the same time. The emission is the average of the measurement results from the three reference fields.

The seasonally integrated emission factor $BF_{BL,s,g}$ (baseline) and $EF_{P,s,g}$ (project) shall be derived as average value from the three measurements for each group.

Hefei Luyu, as the project proponent, prepares a detailed plan for the seasonal methane measurements before the start of the season. The plan for field measurement and laboratory analysis is shown in Section 4.4.

Calculation of the emission rate for a plot (reference field)

- (1) For each gas analysis, calculate the mass of CH₄ emissions with the help of the following formula:

$$m_{CH_4} = c_{CH_4,t} \times V_{chamber} \times M_{CH_4} \times \frac{1atm}{R \times T_t \times 1000} \quad (16)$$

Where:

Parameters	Description
m_{CH_4}	Mass of CH ₄ in chamber at time t (mg)
t	Point of time of sample (e.g. 0,15,30 in case of three samples within 30 minutes)
$c_{CH_4,t}$	CH ₄ concentration in chamber at time t, from gas analysis (ppm)
$V_{chamber}$	Chamber volume (L)
M_{CH_4}	Molar mass of CH ₄ : 16g/mol
$1atm$	Assume constant pressure of 1atm, unless pressure measurement is installed
R	Universal gas constant: 0.08206 L atm/K ⁻¹ *mol ⁻¹
T_t	Temperature at time t (K)

- (2) Determine the slope of the line of best fit for the values of over time with the help of software (e.g. Excel):

$$s = \frac{\Delta m_{CH_4}}{\Delta t} \quad (17)$$

Where:

Parameters	Description
s	Slope of line of best fit (mg/min)

- (3) Calculate the emission rate per hour for one chamber measurement:

$$RE_{ch} = s \times \frac{60min}{A_{chamber}} \quad (18)$$

Where:

Parameters	Description
RE_{ch}	Emission rate of chamber ch (mg/h*m ²)
ch	Index for replicate chamber on a plot
$A_{chamber}$	Chamber area (m ²)

(4) Calculate the average emission rate of a chamber measurement per plot:

$$RE_{plot} = \frac{\sum_{ch=1}^{ch} RE_{ch}}{Ch} \quad (19)$$

Where:

Parameters	Description
RE_{plot}	Average emission rate of a plot (mg/h*m ²)
Ch	Number of replicate chambers per plot

(5) Further procedure: from the average emission rates per plot of each chamber measurement, derive the seasonally integrated emission factor by integration of the measurement results over the season length. The simplest way of integration is multiplying the emission rate with the number of hours of the measurement interval (e.g. one week) and accumulating the results of every measurement interval over the season. Convert from mg/m² to kg/ha by multiplying with 0.01.

Monitoring team

The monitoring team consists of the project proponent, Shanghai Libra Investment Management Co., Ltd, technicians and experts from the agricultural bureau. Firstly, Shanghai Libra sets the monitoring boundary, the number of plots, and draft cultivation logbooks, tables, etc. Secondly, project proponent and Shang Libra confirm the monitoring frequency and notify the technicians and the agricultural bureau. Finally, the monitoring results will be double-checked by experts of the agricultural bureau.




Figure 5-1 The figure of the monitoring team

Monitoring of boundary

The coordinate of the project boundary which encompasses the rice fields where the cultivation method and water regime are changed should be measured and managed strictly in accordance with regulations and saved as KML files. Boundary information such as original records needs to be stored in both electronic and printed archive by the project proponent. Besides, the participants should keep a backup. Files need to be saved at least two years after the end of the crediting period.

In order to obtain valid and reliable boundary information, the monitoring team needs to use the KML or other verified methods to verify the project boundary. If the actual boundary is larger than the boundary in the project design, the excess section is not included in the project boundary; instead, if the actual border boundary is smaller than the boundary in the project design, project boundary should be based on the actual boundary. If there are any changes to the boundary, the modified KML files must be provided.

During the crediting period, project proponents shall assure that the project reference fields are cultivated in a way that they represent the ranges of cultivation practice elements on the project fields in a conservative manner with respect to methane emissions. Should farmers relevantly deviate from the defined project cultivation practice, so that their fields cannot be deemed to be represented by the reference fields any more, those fields shall not be taken into account for the determination of the aggregated project area $A_{s,g}$ of that season. This requirement shall assure that only those farms are considered for the calculation of emission reductions which comply with the project cultivation practice.

Determine the reference fields

The reference fields are fixed rice paddies with area of around 0.3 ha. The baseline reference fields should be selected that they are representative of baseline scenario where double-cropping rice is planted by continuously flooded method without any organic amendments.

Monitoring frequency

The monitoring of the project implementation will take place every year after the project registration in order to ensure the continuity of the benefits.

Data management

All data collected as part of monitoring is archived electronically. All information should be stored by the technology department of the project proponent and all the materials have physical copies for backup. All data collected shall be archived at least two years after the end of the last crediting period of the project activity.

QA/QC

A systematic internal review and correction process will be used to assure/control the quality. The technicians are required to collect the logbooks from farmers once a month and cross check the data with experts. Similarly, the process of monitoring is also supervised by experts. When they find some unusual data, they will feed back to technicians and then correct the data before share it with Shanghai Libra. Shanghai Libra will draft the monitoring report based on the raw data and cross-check with the agricultural bureau experts. If there are not any further comments from the experts, Shanghai Libra will finalise the report. All parties are required to reply any questions raised within 30 days. The monitoring equipment should be updated annually if there are new versions or more efficient monitoring tools available. The agricultural bureau is responsible for monitoring equipment renewal or update.